





## **Dell PowerEdge R320**

An enterprise-class, 1-socket server, the Intel-powered Dell<sup>™</sup> PowerEdge<sup>™</sup> R320 has the right computing power, scalability and value in a dense chassis.

The Dell PowerEdge R320 is an enterprise-class, 1-socket, 1U rack-mount server designed to deliver the right combination of performance, redundancy and value in a dense chassis. This rack server caters to the growing need for virtualization by offering scalable processor performance, a large memory footprint and the capacity for up to eight hard drives. The performance per cost, along with configuration flexibility, storage connectivity and straightforward systems management make the R320 highly appealing to hosting providers. Consistent worldwide support makes the R320 highly appealing to multinational businesses and organizations.

# Enterprise features, scalable expandability and value in a dense chassis

The R320 features the scalable performance of the Intel<sup>®</sup> Xeon<sup>®</sup> E5-2400 processors with essential Intel memory RAS features. This server complements its processors with six DIMMs and two PCI Express<sup>®</sup> (PCIe) slots, providing a substantial memory footprint and wide I/O bandwidth to support both memory-sensitive applications and databases. These combined technology features enable the R320 to support consolidated and virtualized environments.

To protect your virtualized workloads, the R320 offers dual SD cards making your hypervisors redundant and failsafe. Other reliability and availability features include up to four 3.5-inch or eight 2.5-inch hot-plug hard drives, both hardware and software RAID options and redundant, hot-plug power supplies.

#### Ideal for your applications

The R320 is an excellent fit for web, file and print serving as well as smaller scale hosting and e-commerce, retail server, workgroup server and smaller scale virtualization in space-constrained, small-medium business locations and departmental and remote sites of large businesses and public organizations.

#### Enterprise-class network options

As a 1-socket rack server, the R320 has very aggressive advanced network options, carrying multiple third-party brands and adapter types with 10GbE NIC, 10GbE FCoE and Fiber Channel 8Gb HBA.

#### The PowerEdge server line

The PowerEdge family is engineered with the right combination of features and performance scalability to handle tough workloads for both large and small data center environments.

The Dell OpenManage<sup>™</sup> systems management portfolio includes integrated Dell Remote Access Controller (iDRAC) with Lifecycle Controller. This embedded feature helps IT administrators manage Dell servers in physical, virtual, local and remote environments, operating in-band or out-of-band, with or without a systems management software agent. OpenManage integrates and connects to third-party systems management solutions so you can maintain your single point of control and capitalize on your existing investment. OpenManage simplifies the lifecycle of deploying, updating, monitoring, and maintaining your Dell PowerEdge servers.

### PowerEdge R320

- Enterprise computing with
   Intel Xeon processors E5-2400
- Up to eight 2.5-inch drive capacity
- Up to six DIMMs with RAS
- PCIe 3.0-enabled expansion slots
- Enterprise redundancy and scalable expandability

| Feature                               | PowerEdge R320 technical specification  |  |
|---------------------------------------|---|--|
| Form factor                           | 1U rack   |  |
| Processors                            | Intel® Xeon® processor E5-2400 product family<br>Intel Xeon processor E5-1410<br>Intel Pentium® processor 1400 product family   |  |
| Processor sockets                     | 1   |  |
| Internal interconnect                 | Intel DMI 2.0   |  |
| Cache                                 | 2.5MB per core; core options: 2, 4, 6, 8  |  |
| Chipset                               | Intel C600 series   |  |
| Memory <sup>1</sup>                   | Up to 96GB (6 DIMM slots): 2GB/4GB/8GB/16GB DDR3 up to 1600MHz  |  |
| I/O slots                             | <ul> <li>2 PCIe slots:</li> <li>One x8 PCIe slot with x4 bandwidth, half-length, half-height</li> <li>One x16 PCIe slot with x16 bandwidth, half-length, full-height</li> </ul>   |  |
| RAID controller                       | Internal controllers:<br>PERC S110 (SW RAID)<br>PERC H310<br>PERC H710  | <b>External HBAs (RAID):</b><br>PERC H810<br><b>External HBAs (non-RAID):</b><br>6Gbps SAS HBA |
| Drive bays                            | Up to eight 2.5" hot-plug SAS, SATA or SSD or four 3.5" SAS, SATA   |  |
| Maximum internal storage <sup>1</sup> | Up to 12TB  |  |
| Hard drives                           | Hot-plug hard drive options:<br>2.5" SATA, nearline SAS, SAS (15K, 10K), SAS SSD, SATA SSD<br>3.5" SATA, nearline SAS, SAS (15K)<br>Cabled hard drive options:<br>3.5" SATA, nearline SAS, SAS (15K)<br>Self-encrypting drives available  |  |
| Embedded NIC                          | Broadcom® 5720 GbE dual port  |  |
| Power supply                          | Silver efficiency, hot-plug, redundant 350W power supply<br>Bronze efficiency, cabled 350W power supply<br>Auto-ranging power supplies  |  |
| Availability                          | High-efficiency, hot-plug, redundant power supplies; hot-plug hard drives; TPM; dual internal SD support; fan fault tolerance; optional bezel; luggage tag; ECC memory, interactive LCD screen; ENERGY STAR® compliant  |  |
| Remote management                     | Basic management (default)<br>iDRAC7 with Lifecycle Controller<br>iDRAC7 Express (upgrade option), iDRAC7 Enterprise (upgrade option)<br>8GB or 16GB vFlash media (upgrade options)   |  |
| Systems management                    | IPMI 2.0 compliant<br>Dell OpenManage™ Essentials and Dell Management Console<br>Dell OpenManage Power Center<br>Dell OpenManage Connections:<br>• OpenManage Integration Suite for Microsoft® System Center<br>• Dell plug-in for VMware® vCenter™<br>• HP Operations Manager, IBM Tivoli® Netcool®, and CA Network and Systems Management           |  |
| Rack support                          | ReadyRails™ sliding rails with optional cable management arm for 4-post racks (optional adapter brackets required for threaded hole racks)  |  |
| Operating systems                     | Microsoft Windows Server® 2008 R2 SP1, x64 (includes Hyper-V™ v2)<br>Microsoft Windows® Small Business Server 2011<br>SUSE® Linux®Enterprise Server<br>Red Hat® Enterprise Linux<br>Optional embedded hypervisors:<br>Citrix® XenServer™<br>VMware vSphere™<br>For more information on the specific versions and additions, visit Dell.com/OSsupport. |  |
|                                       | r or more information on the specific versions and additio  | ль, мыс Бешсонн/Оззиррон.  |

<sup>1</sup> GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.

#### Global services and support

Dell Services can help reduce IT complexity, lower costs, and eliminate inefficiencies by making IT and business solutions work harder for you. The Dell Services team takes a holistic view of your needs and designs solutions for your environment and business objectives while leveraging proven delivery methods, local talent, and in-depth domain knowledge for the lowest total cost of ownership.

#### OEM-ready version available

From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com/OEM.

Learn more at Dell.com/PowerEdge © 2012 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, and OpenManage are trademarks of Dell Inc. Intel and Xeon are registered trademarks of Intel Corporation in the U.S. and other countries. Microsoft, Windows, Windows, Server, and Hyper-V are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind.

